



ALTO 100

Synthetic heavy duty paste

PRODUCT INFORMATION

BBLubricants Series ALTO products are highly efficient and environmentally friendly alternatives to conventional oil lubricants usable in a wide field of metal processing. Extend tool life while protecting the material from adverse external influences. It can be used on variety of materials - metal and non-metal (steel, aluminum finish, stainless steel, aluminum, copper etc.) Non-oil film on the material also allows seamless subsequent operations such as welding and handling products. Reduces the cost of the cleaning process - without the use of chemicals and degreaser. Lubricant residues removed with warm water. Non-flammable, not leave stains on the material, odorless and without undesirable effects on the environment. They have no negative impact on the health of workers and the no irritating skin.

APPLICATION

Forming and bending sheet metals and tubes

APPLICATION

Iron, Steel, Aluminum, Zinc, Stainless Steel, Titanium

TECHNICAL DATA

Appearance	White paste
pH	8.15
Density	930 - 1020 kg/m ³
Specific Gravity	0,93 - 1,02
Viscosity	NLGI 1
Boiling Point	± 100 °C
Flash Point	N/A
Residuum	Soft film
Methods	Ideal temperature 15 - 35 °C (59 - 95 °F).
Tooling Clean-up	Effortless water based cleaning or mild alkaline cleaner 109°F (43.3°C)
Guarantee	If there is a problem, ask your representative for consultation, if necessary refund or replacment of the defective product.

ADVANTAGES

- Oil-free
- Absent of chlorine, formaldehyde and pharafine additives
- Creater protection layer
- Increases effectivity
- Prolongs durability
- Applicable at high pressures and temperatures
- Non-toxic and biodegradable
- Washable with warm water
- Prevents corrosion and microbial growth

STORAGE

Product should be stored under cover in clean, dry conditions and protected from frost.

Indoors. Recommended storage temperature is between 5°C (41°F) and 35°C (95°F). A shelf life of twnety four months can be anticipated.

MEASURE

The product is not specified as hazardous waste or pollutant of the environment/water. It is biodegradable. Follow local governmental rules and regulations for waste treatment. The product is not miscible with acids, alkalis or solvents. Devices can be painted with epoxy paint or other coatings injurious surfaces.



We believe all the information contained in this document to be reliable, though accuracy or completeness is not guaranteed. BBLubricants s.r.o. is not responsible for injury, loss or damage, direct or consequential, arising from the use of or inability to use its product, suitability and intended use should be verified. User assumes all risk and liabilities associated with.

BBLubricants s.r.o.

Karla IV. 237 | 68801 - Uherský Brod | Czech republic

Tel +420 572 639 636

Fax +420 725 812 101

Email info@bblubricants.cz

